

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

REC'D 28 NOV 2000

WIPO

PCT

Applicant's or agent's file reference 23573-1	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/US00/00989	International filing date (day/month/year) 14 JANUARY 2000	Priority date (day/month/year) 14 JANUARY 1999
International Patent Classification (IPC) or national classification and IPC IPC(7): G01M 17/02 and US Cl.: 73/146		
Applicant IMAGEMAP, INC.		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of 3 sheets.

☐ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority. (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 0 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of report with regard to novelty, inventive step or industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☐ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 27 JULY 2000	Date of completion of this report 20 SEPTEMBER 2000
Name and mailing address of the IPEA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer WILLIAM OEN Telephone N. (703) 308-5161 <i>Perce Restor</i>

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US00/00989

I. Basis of the report

1. With regard to the elements of the international application:*

- ☒ the international application as originally filed
- ☒ the description:
pages 1-7 , as originally filed
pages NONE , filed with the demand
pages NONE , filed with the letter of _____
- ☒ the claims:
pages 8-10 , as originally filed
pages NONE , as amended (together with any statement) under Article 19
pages NONE , filed with the demand
pages NONE , filed with the letter of _____
- ☒ the drawings:
pages 1-1 , as originally filed
pages NONE , filed with the demand
pages NONE , filed with the letter of _____
- ☒ the sequence listing part of the description:
pages NONE , as originally filed
pages NONE , filed with the demand
pages NONE , filed with the letter of _____

2. With regard to the language, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language _____ which is:

- ☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/or 55.3).

3. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in printed form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.


4. ☒ The amendments have resulted in the cancellation of:

- ☒ the description, pages NONE
- ☒ the claims, Nos. NONE
- ☒ the drawings, sheets/fig NONE

5. ☐ This report has been drawn as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

**Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.



INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US00/00989

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. statement

Novelty (N)

Claims 1-20

YES

Claims NONE

NO

Inventive Step (IS)

Claims 1-20

YES

Claims NONE

NO

Industrial Applicability (IA)

Claims 1-20

YES

Claims NONE


NO

2. citations and explanations (Rule 70.7)

Claims 1-20 meet the criteria set out in PCT Article 33(2)-(4), because the prior art does not teach or fairly suggest the claimed depth measuring probe having the claimed laser range finding system.

----- NEW CITATIONS -----

NONE



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/00989

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G01M 17/02

US CL : 73/146

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 73/146, 146.8, 146.2;33/169B, 172E, 558; 356/4, 156, 167; 345/326, 327, 328, 329, 330, 331, 332, 333, 334, 335

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NoneElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
USPTO APS EAST**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,E	US 6,034,676 A (EGAN et al.) 07 March 2000 (07-03-2000), entire patent.	1-20
A	US 3,918,816 A (FOSTER et al.) 11 November 1975 (11-11-1975), entire patent.	1-20
A	US 4,631,831 A (BACHER et al.) 30 December 1986 (30-12-1986), entire patent.	1-20
A	US 4,526,030 A (VECERA, JR.) 02 July 1985 (02-07-1985), entire patent.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

11 APRIL 2000

Date of mailing of the international search report

21 APR 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

WILLIAM OEN

Telephone No. (703) 308-5161

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C.20231
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 28 September 2000 (28.09.00)	
International application No. PCT/US00/00989	Applicant's or agent's file reference 23573-1
International filing date (day/month/year) 14 January 2000 (14.01.00)	Priority date (day/month/year) 14 January 1999 (14.01.99)
Applicant TRACY, Roger, H. et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:

27 July 2000 (27.07.00)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election
- ☒
- was
-
- ☐
- was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).


The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Diana Nissen
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G01M 17/02	A1	(11) International Publication Number: WO 00/42409 (43) International Publication Date: 20 July 2000 (20.07.00)
(21) International Application Number: PCT/US00/00989 (22) International Filing Date: 14 January 2000 (14.01.00) (30) Priority Data: 60/115,915 14 January 1999 (14.01.99) US (71) Applicant (for all designated States except US): IMAGEMAP, INC. [US/US]; 6220 Bush River Road, Columbia, SC 29212 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): TRACY, Roger, H. [US/US]; Unit 1610, 680 North Lake Shore Drive, Chicago, IL 60611-4485 (US). REEVES, Edwin, H. [US/US]; 58 Lyme Bay, Columbia, SC 29212 (US). RADCLYFFE, Nicholas, J. [GB/GB]; The Old Dairy, Nup End Lane, Wingrave, Buckinghamshire HP22 4PX (GB). LONGDEN, Robert, Mark [GB/GB]; The Yews, Grange Park, Northington, Hampshire SO24 9TG (GB). (74) Agents: HARDAWAY, John, B., III et al.; Nexsen Pruet Jacobs & Pollard, LLP, Post Office Drawer 10648, Greenville, SC 29603-0648 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: HAND HELD PROBE FOR MEASURING TIRE TREAD WEAR



(57) Abstract

A hand-held probe (10) for measuring a tire tread profile comprises a housing (20) with a slit (64) formed parallel to its major axis, a range finder (70) mounted inside the housing (20) in such a way that it can traverse much of the length of the tube while directing light from a laser through a window (60) and onto a tire surface, a bracket (50) that is carried by the proximal end of the tube to enable the user to hold the probe (10) in position against the tire, a serial port (32) for connection with a computer (40), and a handle (30) that houses the batteries for operation and an IR or RF transmitter. The IR or RF transmitter is for transmitting the tire tread profile wirelessly to a computer suitably equipped to receive IR or RF transmissions.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

HAND HELD PROBE FOR MEASURING TIRE TREAD WEAR**1. Priority Claim:**

This application claims the benefit of U.S. Provisional Application No. 60/115,915, filed on January 14, 1999, which is hereby incorporated by reference.

2. Field of the Invention:

The present invention relates to devices for measuring tire tread wear. More specifically, the present invention is a device for determining the tread profile by electro-optical measurements so that tread wear can be quantified.

3. Background of the Invention:

Tire treads are defined by a number of grooves or channels cut into the peripheral portion of the tire. The treads are the portions of the periphery that come into contact with the road.

Tire treads give tires traction in cornering and stopping. Tire treads, however, wear during the course of use. Eventually, treads wear to the point where their ability to provide traction is compromised and the tire needs to be replaced or recapped.

Because tire treads wear slowly, and the amount of wear from day to day or week to week is imperceptible, frequent checking is unnecessary. Yet, unless a tire is checked for the depth of its treads at some reasonable interval, an excessively worn tire can be overlooked. Checking tire tread depth at intervals can allow a reasonably prediction as to when the tire will need to be replaced. Furthermore, such a prediction cannot be made, and, indeed, the amount of tread remaining can be difficult to quantify, without a measurement.

Many states have requirements about the condition of the treads of a tire and require the replacement of tires when they become excessively worn. Fleet managers may have their own internal requirements for replacement of tires that are worn based on tread depth or after a specified number of miles. Simple gauges or rulers are simply not accurate enough. Accurate measurement of tire tread depth is difficult to do without removing the tire and measuring the tread with special electro-optical measuring devices. See for example, the patents of Sube et al issued September 21, 1993, US No. 5,245,867, and Dory et al, issued October 5, 1993, US No. 5,249,460. In order to obtain an accurate measurement, the tire is suspended so that it is not engaging a surface. These devices are expensive and require a good deal of time and effort for checking the depth of the tread of

a single tire. However, there remains a need for accurate tire tread depth measurement that does not have the defects of the prior art and that measures the profile of the tire tread so that tread depth can be quantified

SUMMARY OF THE INVENTION

5 According to its major aspects and briefly recited, the present invention is a probe for measuring the profile of a tire tread. A tire tread profile is a two-dimensional plot of the distance from each point on a fixed reference line running across the tire from side to side to the nearest point on the tire surface. This plot will show the differences in the distances to the line for the treads and the channels and thus the amount of wear on the treads. The
10 hand held probe comprises a housing with a slit formed parallel to its major axis, a handle attached to the proximal end of the housing, a range finder mounted inside the housing in such a way that it can traverse much of the length of the tube while directing light from a laser through a window mounted over the slit, and a bracket that is carried near the proximal end of the tube to enable the user to hold the probe in position against the tire. The output
15 from the device is via a computer port proximate to the handle or an IR or RF transmitter from the end of the handle. Power is supplied to the device by batteries in the handle.

The housing of the probe is placed against the tire with the slit and its window facing the tread. Preferably, the housing has an concave arcuate portion formed therein to define two edges of the housing that can act as supports on either side of the window to rest against
20 the tire. When the device is pushed laterally toward the near side of the tire until it engages the tire, the device is then stabilized and in position to make a measurement. With the housing thus in position, the reference line with respect to the tire is set. The device is activated by pressing an "on" button, causing the range finder to determine the distance from the range finder to the tire as the range finder slowly traverses the length of the
25 housing. The distance data -- in terms of x and y coordinates -- is fed to the computer via either the computer port on the proximal end of the housing or the IR or RF window on the end of the handle. The computer can display the distance to the tread and to channels between treads as output, thus displaying the profile of the tire. A computer suitably programmed with local tread requirements can also determine if the tire is acceptable or not.

30 An advantage of the present device is its simplicity of use. The bracket and arcuate housing make it easy to position against the tire so that it is stable. The computer port that

supports data transmission to a computer make the results of the measurement quickly available to the user via any computer.

Another advantage of the present invention is that it provides a tire tread profile rather than a series of single distance measurements. The profile of a tire provides more information than any single measurement and is a more reliable indicator of tread wear than a series of individual measurements, and quicker to obtain.

The IR or RF window in the base of the handle is still another feature of the present invention. This window makes it possible to avoid use of a cable when operating the present handheld tire tread profiler.

Other features and their advantages will be apparent to those skilled in the art of tread depth measurement from a careful reading of the Detailed Description of Preferred Embodiments accompanied by the following drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings,

Fig. 1 is a perspective view of the probe according to a preferred embodiment of the present invention placed against a tire;

Fig. 2 is a side, cross sectional view of a detail of the housing of the probe of Fig. 1; and

Fig. 3 is a view of a display on the computer on the probe of Fig. 1 with a sample display.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention is a hand-held probe for measuring the depth of tire treads. Tire treads are integral, radial projections about the circumference of a vehicular tire separated by narrow gaps or channels from each other. Fig. 1 illustrates the present probe, indicated by reference number 10 in position for a measurement against a tire 12 with treads 14. Gaps 16 are between treads 14. Probe 10 determines the difference in radial distance between the bottom of gaps 16 and the tops of treads 14 and whether this difference meets whatever preselected requirements are imposed by the user or other authority.

Probe 10 comprises a generally cylindrical housing 20 having a proximal end 22 and a distal end 24. Housing 20 is made of light-weight tubing such as aluminum, steel, plastic such as nylon, or composite materials. A handle 30 is fitted on proximal end 22 and an

on/off button 36. Near handle is serial port 32 for connection to a small computer 40 with display 42 and controls 44 via a cable 26. Computer 40 is preferably of the size of a palmtop computer such as that sold under the brand name PALM PILOT, CASSIOPEIA or PSION. These types of computers can receive data into memory and process them for display and storage in a manner well known in the art. Stored data can later be downloaded to a different computer as desired.

Near proximal end 22 is a bracket 50 for engaging the side of tire 12 for stability and to help in aligning probe 10, as will be described more fully below. Along the major axis of housing 20 is a window 60 having a frame 62 with a slit 64 covered by an optical glass 66 to keep dust and dirt out of housing 20. The length of slit 64 should be just as wide as the widest tire to be encountered.

Housing 20 is hollow, has a concave arcuate shape along one side at 28 and is dimensioned internally to house a distance range finder 70 and a carrier assembly 80 for moving distance finder 70 along window 60 while enabling range finder 70 to measure distance (Y-coordinate) from it to tire 12 as it moves along housing 20 (X-coordinate) when probe 10 is properly positioned against tire 12. Range finder 70 sends measurement data to computer 40 by internal cable 72 for computation and display of results either through serial port 32 or IR (infrared) or RF (radio frequency) transmission window 34 in the base of handle 30. By measuring distance between the reference line, which is defined by the location of the distance finder 70 as it traverses housing 20, and the nearest point on tire 12, the tire profile along its rolling face from side to side can be determined and, by subtraction from the reference, the difference in distance between the top of treads 14 and the bottom of gaps 16. This difference will either meet or not meet a preselected criterion storable in computer 40. Computer 40 may be programmed to apply local criteria to the distance measurement and thus produce an "OK" or "NOT OK" along with the distance 92 and the profile 94, as shown in Fig. 3.

During operation, probe 10 is held against tire 12 with the plane of window 60 parallel to the tangent of tire 12 and the two edges 52, 54 of housing 20 against the surface of tire 12 and bracket 50 against the side of tire 12. This "three-point" contact allows probe 10 to have a complete view of tread 14's cross section and be stable for the measurement.

Stability is important to preserve the integrity of the line of reference to the tire defined by the movement of the range finder 70

Range finder 70, which is mounted on the inside of housing 20 can measure the distance from a reference point to any opaque object directly in front of it. Range finder 70 must have a range of operation not less than one inch in front of it and not more than two inches away from the device; that is, it must be capable of measuring the distance to an object as close as one inch and as distant as two inches away. This range allows range finder 70 to function through the thickness of the glass 64 and still have sufficient range to reach the bottom of a gap between treads of a deep truck tire. Range finder 70 must have very tight field of view so as to be able to accurately detect the edge of treads 14 and not produce false readings taken partially on top of treads 14 and partially in gaps 16.

Range finder 70 employs a diode laser light source 74 and two linear position sensors 76 arranged so as to be able to measure the distance to tire 12 when probe 10 is positioned properly against tire 12. Light source 74 is fitted with optics to produce a tightly focused light spot on tire 12. Light is projected toward tire 12 on a line which is parallel to a tire radius vector. An image of the spot on tire 12 is then focused on the linear position sensor 76. Linear position sensors 76 produce electrical signals proportional to the location of the spot on the sensor surface. The sensor is positioned at an angle to the laser so that the location of the focused spot on the sensor therefore functions as a laser triangulation distance measurement device.

The depth of gap 16 can be large compared to its width. The narrow shape of gap 16 can block the view of a single linear position sensor when the laser spot is at the bottom of gap 16. This problem is most evident when the spot drops into gap 16 with the edge of tread 14 on the same side as that position sensors. To improve measurements on in gaps 16, the present range finder 70 uses two position sensors 76. Sensors 76 are mounted at complementary angles on either side of laser light source 74. This improves the percentage of the width of the bottom of gaps 16 that can be measured.

To measure a complete cross section of tire 12, range finder 70 scans across tire 12's width carried by carrier assembly. Range finder 70 is mounted on a linear bearing 82 and guided with a rod 84 mounted parallel to the central axis of housing 20. A pulley 86, 88, is mounted at each end of rod 84 and motor-driven, toothed belt 90 is fitted between pulleys

86, 83. The motor-driven belt 90 is used to move range finder 70 along the length of rod 84 while measurement is being taken. The motor is not shown since this type of mechanism, similar to that of a printer head carrier is well known to those skilled in the art. See for example US Patent No. 5,162,916. Batteries 98 to power the range finder motor are located in handle 30.

The position of range finder 70 along rod 84 may be measured by a displacement transducer (not shown) or tracked using a stepper motor (not shown) on belt 90.

The tread profile is a data set consisting of points containing an X-coordinate which is the position of range finder 70 on guide rod 84 and a Y-coordinate which is the distance from range finder 70 to the surface of tire 12. These coordinates are transmitted to computer 40 by means of suitable and conventional data link such as cable 72.

Computer 40 can produce a plot of the data points to enable the user to ensure that the unit is functioning correctly. Display 42 shows a first plot 92 of actual distance to tire 12, a second plot 94 showing the difference in distance between a reference point on tread 14, and an indication as to whether the tread depth is sufficient or not according to a preselected criterion. Clearly various output can also be displayed from the received data, such as average and mean tread depth, minimum tread depth, and so on. Specific criteria as defined by local highway regulators may be applied to determine if the tire is passable. The measurements may also be used to predict when tire replacement will be required or the number of miles until tire replacement based on comparison with stored data about a particular tire or tires in general.

In use, probe 10 is placed against the rolling face of a tire 12 and pushed against tire 12 so that bracket 50 engages the side of tire 12 and window 60 is parallel to the tangent of tire 12 where the edges 52, 54, of probe 10 meet tire 12. Range finder 70 and carrier assembly are activated by pressing on/off button 36. Light source 74 on range finder 70 transmits a beam of well focused light onto tire 12 through window 60 and position sensors 76 adjacent light source 74 on range finder 70 perceive the distance from range finder 70 to tire 12. The data reflective of that distance are transmitted through cable 72 to computer 40 where the data is analyzed and displayed on display 42 for the operator.

It will be apparent to those skilled in the art of tread depth measurement that many modifications and substitutions can be made to the foregoing description of preferred

embodiments without departing from the spirit and scope of the present invention, defined by the appended claim.

WHAT IS CLAIMED IS:

1. A probe for measuring tread depth, said probe comprising:
a housing having a window formed therein, said housing having a proximal end and
a distal end;
5 range finding means carried within said housing and oriented so that said range
finder directs a beam of light through said window;
means for moving said range finding means parallel to said window;
means carried by said housing for gripping said housing;
tire-engaging means carried by said proximal end for engaging a side of a tire; and
10 means carried by said housing and in operational connection with said range finding
means and said moving means for sending distance data from said laser range finding means
as said laser range finding means is moved parallel to said window.
2. The probe as recited in claim 1, wherein said housing has an concave arcuate
edge formed at both said proximal end and said distal end to provide support for a tire.
- 15 3. The probe as recited in claim 1, further comprising a communications port means
carried by said gripping means for communicating distance data to a computer.
4. The probe as recited in claim 3, wherein said communications port means
transmits distance data using an infrared transmission.
5. The probe as recited in claim 3, wherein said communications port means
20 transmits measurement data using a radio frequency transmission.
6. The probe as recited in claim 1, wherein said gripping means is a handle carried
by said proximal end of said housing.
7. The probe as recited in claim 3, further comprising a handheld computer, said
handheld computer in electrical communication with said range finding means, said handheld
25 computer having a display and means for plotting distance data.
8. A probe for measuring tread depth, said probe comprising:
a housing having a window formed therein, said housing having a proximal end and
a distal end;
range finding means carried within said housing and oriented so that said range
30 finder directs a beam of light through said window;
means for moving said range finding means parallel to said window;

a handle carried by said proximal end of said housing; and
means carried by said housing and in operational connection with said range finding
means and said moving means for sending distance data from said laser range finding means
as said laser range finding means is moved parallel to said window.; and

5 communications port means carried by said handle for communicating distance data
to a computer.

9. The probe as recited in claim 8, wherein said communications port means
transmits measurement data using an infrared transmission.

10 10. The probe as recited in claim 8, wherein said communications port means
transmits measurement data using radio frequency transmission.

11. The probe as recited in claim 8, further comprising tire-engaging means carried
by said proximal end for engaging a side of a tire.

12. The probe as recited in claim 8, wherein said window is positioned in contact
with the tread of a tire.

15 13. The probe as recited in claim 8, further comprising a handheld computer, said
handheld computer in electrical communication with said range finding means, said handheld
computer having a display and means for plotting distance data.

14. The probe as recited in claim 8, wherein said gripping means is a handle carried
by said proximal end of said housing.

20 15. A method for measuring the tread profile of a tire, said method comprising the
steps of:

scanning the rolling face of a tire to determine the tread profile;
communicating said tread profile to a computer having a display;
plotting the tread profile on said display;

25 16. The method as recited in claim 15, wherein said scanning step and
communicating step is performed by a probe having a handle, said handle having a
communications port that communicates said tread profile to said computer.

30 17. The method as recited in claim 15, wherein said tread profile is communicated
to said computer using a transmission selected from the group consisting of infrared and
radio frequency.

18. The method as recited in claim 15, wherein said scanning step is performed by a handheld probe.

19. The method as recited in claim 15, further comprising the step of determining whether the tread profile complies with the minimum allowable tread profile listed in
5 governmental regulations.

20. The method as recited in claim 19, further comprising the step of predicting when the tire needs replaced to comply with the minimum allowable tread profile listed in governmental regulations.

1/1

FIG. 2






FIG. 1

FIG. 3



JC18 Rec'd PCT/PTO 1 1 JUL 2001